

SELECTION & SPECIFICATION DATA

Type	Tacky Acrylic Emulsion
Description	Blackhawk Hawk-Tack 7000 is a high tack acrylic emulsion primer. It can be applied to masonry, gypsum board, concrete, wood, and a variety of other surfaces. Blackhawk Hawk-Tack 7000 is the product of choice when it is necessary to achieve fast drying, solvent free, tacky surfaces.
Features	<ul style="list-style-type: none"> • Quick drying • Tacky film provides positive adhesion of membranes • Easily applied by brush, spray or roller • Environmentally friendly low VOC • Non-flammable during application • Water-based, no solvent odor
Uses	Blackhawk Hawk-Tack 7000 is designed to be used as a surface adhesion promoter with modified bitumen self-adhering membranes, or where a tacky surface is required.
Color	White. Custom colors available.
Finish	Blackhawk Hawk-Tack 7000 has a tacky/gloss finish. Color tinted material helps to indicate application area.
Solids Content	60 ± 2% by weight
Theoretical Coverage Rate	300 to 400 square feet at 4 to 5 wet mils
VOC Value(s)	<25 grams per liter (0.2 lbs per gallon)
Limitations	Keep from freezing

SURFACE & PRODUCT PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

MIXING & THINNING

Mixing	Mix material before use to ensure uniformity.
Thinning	Use as supplied. Water reducible if situations dictate.

APPLICATION GUIDELINES

Brush	Apply with a wide fiber brush in order to create a smooth uniform film.
Roller	Use a low nap phenolic core roller.

Drying Time Initial set: 30 minutes at 68°F (20°C)
Full set: 2 hours 68°F (20°C)

Application Temperature 45°F – 110°F (7.2°C – 43.3°C)

CLEANUP & SAFETY

Cleanup Mineral spirits

Safety Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.

Ventilation Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

PACKAGING, HANDLING & STORAGE

Shelf Life 6 months when kept at recommended storage conditions and in original unopened containers.

Package Sizes 4 x 1 gallon pail box - 35 lbs
5 gallon pail - 46 lbs
55 gallon drum - 500 lbs
275 gallon tote - 2500 lbs

Storage Temperature & Humidity 50°F – 110°F (4°C – 43°C)
0 – 100% relative humidity

Storage Store Indoors. Protect from freezing.

PHYSICAL PROPERTIES

Flammability	Wet nonflammable, dry burns
Flash Point	>212°F (100°C)
Viscosity	2,000 – 4,000 cps
Weight Per Gallon	8.0 – 9.2 lbs

Rev 06/19

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.