



#### NOTES :

1. FRAME TRENCH DRAINS WITH [ 1 ] ONE ROW OF TILES SET AS SHOWN.
2. WIDTH OF TILE JOINTS DEPEND UPON TYPE OF GROUT OR MORTAR AND SETTING METHOD USED.
3. TILE SURFACE ADJACENT TO TRENCH SHALL BE + 1/16" ELEVATION ABOVE GRATING SEAT.

*This drawing, including the principle of design, is the property of ErgonArmor and is submitted with the understanding that it will not be used for any other purpose except that specified in writing by ErgonArmor. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ErgonArmor expressly disclaims any and all liability as to any results obtained or arising from the use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The user should thoroughly test any application before installation. Nothing contained herein should be taken as an inducement to infringe any patent.*

## CED-608 01/12 SUPERSEDES 12/09 TUFCEM® TILING SYSTEM TRENCH DRAIN DETAIL

NO SCALE  
DRAWN BY: CO  
COPYRIGHT: ErgonArmor

