



# R-17-A-73 Asphalt Coating/Primer

## SELECTION & SPECIFICATION DATA

<b>Type</b>	Oxidized Asphalt Cutback
<b>Description</b>	R-17-A-73 Asphalt Coating/Primer is a metal corrosion protection coating and asphalt primer packaged in a convenient aerosol spray can. It offers a favorable amount of product for small jobs and touch up work.
<b>Features</b>	<ul style="list-style-type: none"><li>• ANSI/NSF 61 certified</li><li>• Quick drying (less than 5 minutes dry-to-touch)</li><li>• Penetrating and sealing primer</li><li>• Packaged in convenient aerosol spray can</li></ul>
<b>Uses</b>	<ul style="list-style-type: none"><li>• Potable water service</li><li>• Ductile iron pipe and fittings (ID and OD)</li><li>• Roofing primer</li><li>• Vehicle underbody</li><li>• Paving maintenance</li><li>• General metal corrosion protection</li></ul>
<b>Color</b>	Black
<b>Finish</b>	Gloss
<b>Topcoats</b>	Asphalt, acrylics, epoxies, polyurethanes. Consult ErgonArmor for more information.
<b>Dry Film Thickness (DFT)</b>	1 – 2 mils per coat

## SUBSTRATES & SURFACE PREPARATION

<b>All</b>	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

## SAFETY

<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
<b>Ventilation</b>	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.
<b>Cleanup</b>	Mineral spirits or equivalent solvent.

## PACKAGING, ESTIMATING & HANDLING

<b>Storage Temperature &amp; Humidity</b>	40°F – 110°F (4°C – 43°C) 0 – 100% relative humidity
<b>Package Sizes</b>	12 cans per case (16 lbs per case) 90 cases per pallet
<b>Theoretical Coverage</b>	40 square feet per can at 2 coats
<b>Storage &amp; Shelf Life</b>	Maintain products in original packaging and sealed until ready for use. Estimated shelf life is 24 months at 75°F (24°C) when kept at recommended storage conditions and in original unopened containers. Store indoors. Always inspect the product prior to use.

Rev 08/21

### **TERMS AND CONDITIONS OF SALE**

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).